

DIVINE EST 1994 ATER

b5

Beautifully

refreshing.

### A design like no other

The B5 range straddles the line between high-end functionality and ultra-modern design. The unique streamlined design of this range will bring sophistication to any environment.

#### Reasons to choose

- Optimum height for interaction
- Fully open, illuminated dispense area
- Shrouded faucet for hygienic protection
- Compact, alarmed drainage system
- Built-in leak detector



Water system



Direct Chill

Configuration



Floorstanding

Number of users

Water options



Chilled



Available colours









#### Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



Ultra-violet sterilising system
For added hygiene confidence,
appliances can be fitted with
Viovandt™ – an ultra-violet
sterilisation process that
reduces water-born bacteria.



Sterizen is a registered trademark



Fynil is a registered trademark

#### Biofilm, limescale and impact resistant epoxy resin panel finish

Providing an increased level of hygiene and longevity, Fynil™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.

B5 Models	Silver	
Direct Chill, Floorstanding		
Chilled, Ambient	101520	
Chilled, Ambient, Sparkling	101530	
Chilled, Ambient, Hot	101540	
Chilled, Hot, Sparkling	101550	

Power requirements
Hertz 50/Volts 220-240

Max power consumption

Chilled & Ambient 100W
Chilled, Ambient & Sparkling 140W
Chilled, Ambient & Hot 900W
Chilled, Hot & Sparkling 940W

Chilled temperature
Min 2°C/Max 11°C

Hot temperature

Max 92°C Throughput litres per hour

Chilled 35/Hot 6

Dimensions
Floorstanding
Dispense height

WxDxH 520x415x1310mm 250mm





Talk to an adviser:

01892 669609

sales@divinewater.co.uk

www.divinewater.co.uk