

borg &
overström

f4



Robust and simplistic

Where functionality and style merge,
bringing a robust and timeless drinking
solution to any environment.



Power requirements
Hertz 50/Volts 240
Max power consumption
120W

Chilled Temperature
Min 2°C/ Max 11°C
Throughput litres per hour
Chilled 40

Dimensions	WxDxH
Floorstanding	360x270x1230mm
Dispense height	220mm

Key Features

- Robust stainless steel finish
- Direct Chill cooling system
- Up to 40 litres per hour output
- Simple to use and easy to maintain
- Solid construction

Available accessories

- Waste Kit
- Bottle Filler Blanking Plate
- Wall & Floor Bracket Set
- Waste Pump Kit
- Sanitisation Kit
- Install Kit with Filter
- Blue Tint Cups (7oz)




Water options



Chilled

Configuration



Floorstanding

Recommended environment



Industrial



Healthcare



Education



Leisure

Number of users



6-10



11-25



25+

f4 Models

Direct Chill, Floorstanding, Chilled - 401841

Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone
+44 (0)1362 695 006
Email
sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838134
Version: 13012015